










RIVA 3 / RIVA-E 3

Side shredder working width from 1400 to 2200 mm










The RIVA 3 shredder is designed for professional use. It is suitable for the maintenance of road sides, banks, ditches and hedges. The shredded residues are ejected behind the self-cleaning support roller. The machine moves on self-lubricating metal bushings.



RIVA 3 - MODEL 2911 - INTERNAL GEAR-BOX

CODE	 mm	 mm								B	C	D	E		
			kw	hp	kg	n°	n/1'	kg	n°	n°	n°				
2911.140	1400	1580	55	75	2100	3	540	530	3	16	32	2000	900	2350	1300
2911.160	1600	1780	60	80	2200	3	540	580	3	20	40	2000	900	2350	1500
2911.180	1800	1980	63	85	2300	4	540	610	3	20	40	2000	900	2350	1700
2911.200	2000	2180	66	90	2400	4	540	650	3	24	48	2000	900	2350	1900
2911.220	2200	2380	69	95	2500	5	540	700	3	24	48	2000	900	2350	2100

RIVA-E 3 - MODEL 2912 - EXTERNAL GEAR-BOX

CODE	 mm	 mm								B	C	D	E		
			kw	hp	kg	n°	n/1'	kg	n°	n°	n°				
2912.140	1400	1890	55	75	2300	3	540	550	3	16	32	2000	560	2650	1600
2912.160	1600	2090	60	80	2400	3	540	600	3	20	40	2000	560	2850	1800
2912.180	1800	2290	63	85	2500	4	540	630	3	20	40	2000	560	3050	2000
2912.200	2000	2490	66	90	2600	4	540	670	3	24	48	2000	560	3250	2200
2912.220	2200	2690	69	95	2700	5	540	690	3	24	48	2000	560	3450	2400

STANDARD EQUIPMENT

- 540 rpm free wheel gearbox
(external gear box for the E version)
- Forged hammer blades
- Body with rounded corners and protections
- Double body
- Adjustable support roller Ø 194 mm
- 3-point hitch linkage Cat. 2
- Mechanical anti-shock system
- Hydraulic jacks with speed adjustment
- Cardan shaft
- CE protection

